

## WOCO CIRCULATING OIL 8220

Woco Circulating Oil 8220 is blended with premium quality, highly refined base stocks. It has excellent resistance to oxidation and rust and is formulated with a unique demulsifier to enhance water separation characteristics. Woco Circulating Oil 8220 can be used in any application calling for an ISO 220 general purpose non-antiwear lubricating oil. This product is designed to meet or exceed Morgan Morgoil lubricant specifications, including the Morgan “super demulsibility” advanced lubricant specification.

### ASTM D1401 Water Separability

Oil (mL) .....	40.0
Water (mL) .....	40.0
Emulsion (mL).....	00.0
Time (min).....	10.0

### ASTM D2711 Demulsibility

Free Water (mL).....	38.00
Centrifugal Water (mL).....	01.10
Total Water (mL).....	39.10
Water in Oil (mL).....	00.20
Emulsion (mL) .....	00.00
Test Temperature (°C).....	82.00

### ASTM D892 Foaming

Sequence I.....	0 - 0
Sequence II .....	0 - 0
Sequence III .....	0 - 0

### TYPICAL PROPERTIES

ISO Grade.....	220
Gravity, °API .....	26.1
Viscosity @ 40°C, cSt.....	220
Viscosity Index.....	90
Flash Point, °C.....	215
Pour Point, °C.....	-12
Copper Strip Corrosion.....	1a

**PAGE#2**

**SHIPPING CONTAINERS**

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

**HEALTH & SAFETY**

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

**WARRANTY**

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.