

## **PROCUT 82**

### **GENERAL DESCRIPTION**

PROCUT 82 is a cutting oil that is chlorine-free and contains inactive sulfur. It has excellent boundary lubrication and contains a special additive package that provides outstanding cutting properties and tool life. PROCUT 82 is recommended for use on stainless steel, ferrous, and non-ferrous metals. This versatile cutting oil is suitable for turning, reaming, and many other metal cutting applications. It was designed for use in making intricate parts for the medical and aerospace industries.

PROCUT 82 is easy to wash off finished parts and does not stain copper or copper alloys. For the operator's ease of visibility and for general cleanliness, this oil has been formulated to be transparent and light in color. PROCUT 82 has less tendency to smoke than many competitive cutting oils, has good resistance to oxidation, and helps maintain low mist levels.

### **TYPICAL PROPERTIES**

Viscosity @ 100°F.....	90 - 115
Gravity, API.....	28.5
Lubricity Additives .....	Present
Chlorine .....	None
Inactive Sulfur .....	Present
Flash point COC °F.....	330

### **SHIPPING CONTAINERS**

Available in 5 gallon pails, 55 gallon drums, 275 gallon totes, or bulk delivery.

### **HEALTH & SAFETY**

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

### **WARRANTY**

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.