

PROCUT SSLV

GENERAL DESCRIPTION

PROCUT SSLV is a heavy-duty amber colored cutting oil. It contains sulfur, chlorine, wetting and anti-weld agents, along with premium base oils. PROCUT SSLV has been specially formulated with a low volatility fatty additive that has proven itself far superior to previous fatty oil technology. This combination of additives provides excellent extreme pressure properties when pipe threading, tapping, reaming, or broaching. PROCUT SSLV is designed for the most demanding metal removal applications. It is particularly well suited for machining stainless steels. PROCUT SSLV has low misting properties, an effective defoamer package, and contains no active sulfur. It can be used on copper and its alloys and as a dual-purpose oil.

TYPICAL PROPERTIES

Viscosity @ 100°F, SUS.....	120
Flash Point, °F.....	360
Pour Point, °F.....	10
Color, ASTM.....	4.5

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.