

WOCO TURBINE & HYDRAULIC 32

GENERAL DESCRIPTION

Woco Turbine & Hydraulic Oil 32 is a highly refined distillate oil that has excellent thermal and oxidation stability, rust protection, anti-foam and demulsibility. Woco Turbine & Hydraulic Oil 32 is recommended for turbine lubrication, machine tools, circulating oil systems and hydraulic systems operating at less than 1000 psi and/or less than 1200 rpm.

TYPICAL PROPERTIES

Viscosity, cST @ 40°C	32
Viscosity, cST @ 100°C	5.4
Viscosity Index	95
API Gravity	31
Pour Point °F	-10
Flash Point COC °F	400
Cu Corrosion	1B
Emulsion Test	Pass
Rust Test	Pass
Demulsibility, ASTM D1401.....	40/40/0 (20 minutes)

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.