

WS 3350

GENERAL DESCRIPTION

WS 3350 is formulated to be a specialty tube mill coolant. It contains wetting agents designed to keep the rolls clean by increased sheeting action, without the conventional lubricity increases that can lead to slippage. It has a high degree of bio-stability, and copper stain inhibition, as well as excellent rust protection especially in the face of higher chloride levels. This product does not contain sulfurized or phosphorus-containing additives, DEA, or secondary amines.

PERFORMANCE BENEFITS

- Excellent Iron, Steel, and Copper protection
- Improved wheel life due to increased wetting
- Non-Tacky Residue
- Excellent Sump Life
- Operator Friendly

TYPICAL PROPERTIES

Appearance.....Clear Blue Liquid
 pH Value, 5% solution.....9.3
 Density, lbs/gal..... 8.645
 Refractometer Factor..... 4.5

RECOMMENDED CONCENTRATION

REFRACTOMETER READING

Forming..... 5 - 10 % 1.1 - 2.2

CONCENTRATION CALCULATION

% Concentration = Refractometer Reading x Refractometer Factor

Note: Always calibrate the refractometer so that it reads 0.0 with water that will be mixed with the machining coolant.

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of a product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.