

WOCO HEP GEAR OIL 68

GENERAL DESCRIPTION

Wallover HEP gear oils are premium quality extreme pressure gear lubricants formulated with high viscosity index base oils. These products contain a sulfur-phosphorus additive package and do not contain lead. Wallover HEP gear oils possess good adhesion properties, are non-corrosive and are foam inhibited. They resist oxidation, are thermally stable and have good demulsibility. They are recommended for circulating, splash, bath or spray lubrication systems on enclosed gear, chain or sprocket drives.

TYPICAL PROPERTIES

AGMA GRADE.....	2 EP
VISCOSITY, cST @ 40°C.....	70
cST @ 100°C.....	8.7
VISCOSITY INDEX.....	90
API GRAVITY.....	30
FLASH POINT, COC°F.....	415
Cu CORROSION.....	1B
TIMKEN EP, lbs.....	60
CLEANLINESS, ISO.....	20/18/14
FZG PASS STAGE.....	12

SHIPPING CONTAINERS

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

HEALTH & SAFETY

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

WARRANTY

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.