

## **WOCOCUT SM 165**

### **GENERAL DESCRIPTION**

WOCOCUT SM 165 is excellent tri-purpose oil for automatic screw machines, providing good cutting properties and excellent internal lubrication. It may be used to cut both ferrous and non-ferrous metals. In addition to wetting agents and anti-weld additives, WOCOCUT SM 165 contains a complete additive package to provide anti-wear, detergency, anti-misting characteristics, oxidation stability, anti-rust, anti-foam, and high temperature hydrolytic stability. WOCOCUT SM 165 is fully fortified as an anti-wear lubricant, and can be used with confidence in lubrication systems with operating pressures above 1000 pounds P.S.I.

### **TYPICAL PROPERTIES**

Viscosity @ 100°F, SUS.....	165
Flash Point, °F .....	400
Pour Point, °F .....	10
Gravity, API .....	29
Lubricity Additives .....	Present
Extreme Pressure Additives .....	Present
Cleanliness, ISO .....	17/15/12

### **SHIPPING CONTAINERS**

Available in 5 gallon pails, 55 gallon drums, or 275 gallon bulk containers.

### **HEALTH & SAFETY**

Material Safety Data Sheets are available for all Wallover products. Consult the MSDS for information regarding the storage, handling and disposal of this product.

### **WARRANTY**

All reasonable effort has been made to ensure that the information provided in this publication is accurate. No warranties are expressed or implied since the use of this product is beyond our control.